1

TITLE OF THE INVENTION

ON-CHIP EMULATOR COMMUNICATION

FIELD OF THE INVENTION

5   The present invention relates to a system and method for communicating with an embedded digital processor on a single integrated circuit chip, the chip comprising an on-chip emulation device.

BACKGROUND TO THE INVENTION

10   In a first debugging technique, a hardware emulator program is provided on the host computer which is performing the debugging. Such emulators however can only provide limited functionality, and are generally
15 undesirable.

        In a technique used by the Applicants for communicating with embedded digital processors, so-called "on-chip emulators" are used. The function of an on-chip
20 emulator device is to monitor and control the operation of the digital signal processor. Such devices typically have storage capability, and are able to initiate command and control sequences for the digital processor in response to externally applied signals from a host
25 computer or in response to detected states of the digital processor.

        Communication between the on-chip emulation device and the host computer is carried out via a link, which is
30 typically a link designed for that purpose. Typically, signals over the link are tailored to the particular on-chip emulation device in the interests of efficient debugging.

This however is an inflexible arrangement, and is typically limited to use during "pure" debugging - i.e. pre-production debugging. It would not be suitable for

5   production use, or where the need arises for communication with an embedded system while it is in service - eg to update data or programs stored on the embedded system.

10 SUMMARY OF THE INVENTION

It is an object of the present invention to provide a system and method capable of improved communication with an integrated circuit chip containing an embedded digital processor.

15

According to a first aspect of the present invention there is provided a method of communicating with an integrated circuit chip having plural components thereon, said components including digital processing circuitry

20 and an on-chip emulator connected to said digital processing circuitry for initiating command and control sequences for the digital processing circuitry in response to externally applied signals or in response to detected states of the digital processing circuitry, the

25 method comprising:-

providing a universal serial bus having first and second ends, said first end being connected to said on-chip emulator;

providing a computer device having a digital

30 processor, a universal serial bus port connected to said second end of said universal serial bus, and a second port for connection to a communication channel;

assigning at least one of said components with a respective address;

sending a remote procedure call from component over said universal serial bus to said computer device;

5   in response thereto, causing said computer device to generate a socket call over said communication channel thereby creating a first socket at said computer device and a second socket at a computer connected to said communication channel;

10   in said computer device, receiving a response at said first socket; and

sending information derived from said response to said component.

15   According to a second aspect of the invention there is provided a method of communicating with an integrated circuit chip having plural components thereon, said components including digital processing circuitry and an on-chip emulator connected to said digital processing

20   circuitry for initiating command and control sequences for the digital processing circuitry in response to externally applied signals or in response to detected states of the digital processing circuitry, the method comprising:-

25   providing a universal serial bus having first and second ends, said first end being connected to said on-chip emulator;

providing a computer device having a digital processor, a universal serial bus port connected to said

30   second end of said universal serial bus, and a second port for connection to a communication channel;

assigning plural of said components with a respective address;

sending a remote procedure call from one of said plural components over said universal serial bus to said computer device, including data indicative of another of said plural components;

5   in response thereto, causing said computer device to generate a socket call over said communication channel thereby creating a first socket at said computer device and a second socket at a computer connected to said communication channel;

10   in said computer device, receiving a response at said first socket; and

sending information derived from said response to said another component.

15   Preferably the method further comprises implementing a proxy server process in said computer device, wherein said proxy server process implements said causing and sending steps.

20   Advantageously said communication channel comprises an Ethernet link.

Conveniently said communication channel comprises a telephone link.

25

According to another aspect of the invention there is provided a system for communicating with an integrated circuit chip having plural components thereon, said components including digital processing circuitry and an

30   on-chip emulator connected to said digital processing circuitry for initiating command and control sequences for the digital processing circuitry in response to externally applied signals or in response to detected

states of the digital processing circuitry, the system
comprising:-

    a universal serial bus having first and second ends,
said first end being connected to said on-chip emulator;

5   a computer device having a digital processor, a
universal serial bus port being connected to said second
end of said universal serial bus, and a second port for
connection to a communication channel;

    generating circuitry associated with said component

10   for sending a remote procedure call from said component
over said universal serial bus to said computer device,
wherein said remote procedure call comprises data
indicative of said component;

    conversion circuitry in said computer device for

15   generating a socket call over said communication channel
in response to a received remote procedure call thereby
creating a first socket at said computer device and a
second socket at a computer connected to said
communication channel;

20   receiving circuitry in said computer device for
receiving a response at said first socket; and

    sending circuitry for sending information derived
from said response over said universal serial bus to said
component.

25

    Accroding to a further aspect of the invention there
is provided a system for communicating with an integrated
circuit chip having plural components thereon, said
components including digital processing circuitry and an

30   on-chip emulator connected to said digital processing
circuitry for initiating command and control sequences
for the digital processing circuitry in response to
externally applied signals or in response to detected

states of the digital processing circuitry, the system
comprising:-

a universal serial bus having first and second ends,
said first end being connected to said on-chip emulator;

5   a computer device having a digital processor, a
universal serial bus port connected to said second end of
said universal serial bus, and a second port for
connection to a communication channel;

generating circuitry for sending a remote procedure
10   call from one of said plural components over said
universal serial bus to said computer device, including
data indicative of another of said plural components;

conversion circuitry in said computer device for
generating a socket call over said communication channel
15   in response to a received remote procedure call thereby
creating a first socket at said computer device and a
second socket at a computer connected to said
communication channel;

receiving circuitry in said computer device for
20   receiving a response at said first socket;   and

sending circuitry in said computer device for
sending information derived from said response to said
another component via said universal serial bus.

25   Preferably said computer device comprises an
interface device having a universal serial bus port and
an Ethernet port for connection to a computer network,
whereby said communication channel comprises said
computer network.

30   Advantageously said communication channel comprises
a telephone link.

Conveniently said communication channel comprises
the Internet.

BRIEF DESCRIPTION OF THE DRAWINGS

An exemplary embodiment of the invention will now be described with reference to the accompanying drawings in which:-

5   Figure 1 shows a schematic diagram of an integrated circuit chip having an on-chip emulator device and a USB interface;

Figure 2 shows a multiprocessor version of the chip of Figure 1 and;

10   Figure 3 shows a partial block schematic diagram of a communication system in accordance with the present invention.

In the various figures, like reference numerals

15   indicate like parts.

DESCRIPTION OF PREFERRED EMBODIMENTS

Referring first to Figure 1, an embedded system includes an integrated circuit chip 100 which comprises a

20   processor 10 on said chip. As used herein, the term 'processor' includes microprocessors and digital signal processors. The processor is connected to other component circuitry of said embedded system in a manner known to those skilled in the art.

25

It may be advantageous to be able to collect information about the operation of the processor and also to supply control and command information to said processor, both in response to conditions on the

30   processor itself, and also in response to information conveyed from a host computer. Such a situation may be used not only during debugging, but also may allow

updating of program data, and configuration of intelligent peripherals.

For collecting information about operation of the processor and for controlling the processor, the chip 100 includes an on-chip emulator having storage and processing circuitry for that purpose. Such an on-chip emulator 20 is shown schematically on Figure 1 as having a control path 21 connected to the processor 10 and having an information-collecting path 22 from the digital processor 10.

The on-chip emulator 20 has associated JTAG circuitry 30 connected to it.

To enable ready connection to a host device, the chip further comprises a universal serial bus (USB) interface circuit 40. The USB interface 40 has a first port 41 connected to the on-chip emulator 20, a second port 42 connected on-chip to a USB port 50 via a universal serial bus 51. The USB interface circuitry also has a further port 42 connected to the JTAG circuitry 30 which in turn has an on-chip connection 31 to a JTAG port 60.

A universal serial bus is, in use, connected to the USB port 50. For debug purposes, the universal serial bus 52 connects at its other end to a host device having a USB port.

Debugging may take place using the host device itself; however by virtue of the USB connection, it may

be possible to debug from a more remote location, as will
be later described herein.

Referring now to Figure 2, a second integrated
5   circuit chip 200 comprises plural - here 3 - embedded
processors 110, each having a respective associated on-
chip emulator 120 connected to it via a respective
control path 121 and information collecting path 122.
Each on-chip emulator 120 is connected to respective USB
10   interface circuitry 140 and each USB interface circuitry
140 has a USB input port 142 to which is connected an on-
chip universal serial bus 151 which connects to a USB hub
170.   JTAG circuitry as shown in Figure 1 is also
provided but is not shown for the sake of clarity.
15

The USB hub 170 has an input for a universal serial
bus 152, for off chip communication.

Referring to figure 3 an embodiment of the present
20   invention will now be described.

A target device 100, as described with respect to
figure 1, is connected via a communication device 700 to
a host computer system 800. The communication device 800
25   has an Ethernet port 750, a universal serial bus port 710
and an integrated circuit chip 701 having on-chip
processing circuitry 720, on-chip memory circuitry 721,
an on-chip Ethernet interface 740 and an on-chip
universal serial bus interface 730.   The on-chip Ethernet
30   interface is connected to said Ethernet port via wiring
741, and the universal serial bus interface is connected
to the universal serial bus port via wiring 731. The
Ethernet port 750 connects to the host via a link 751. It

will be understood that the link 751 may be a direct link
or a network connection, or any other functionally
transparent link. Thus the host could be remote and
connected via a Local Area Network, or other network, and
5 the Ethernet port be local and coupled to the network.

Connections located on the chip link the interfaces
to the processing circuitry so that data incoming to the
Ethernet port 750 are translated from the Ethernet
10 protocol to the form required by the processing circuitry
720. Any data to be sent to the target device is output
by the processing circuitry 720 to the universal serial
bus interface and there translated to the universal
serial bus protocol and transferred via the universal
15 serial bus 52 to the target.

In use the on-chip processing circuitry 720 operates
using embedded web server processes and the communication
device forms an intelligent networked device. The
20 consequence is that it is possible to move certain
selected processes from the host onto the on-chip
processing circuitry 720. Typically processes suitable
for implementation on the on-chip processing circuitry
include those that need frequent interaction with the
25 target.

Continued reference to Figure 3 shows that the
communication device 700 has a further port 760, for
connection to a telephone line. To provide data of the
30 right form for signalling over a telephone line, the
processing circuitry 720 may form a soft modem or
alternatively an on-chip hard modem may be provided, as
known to those skilled in the art.

Use of the telephone line port 760 enables connection to the Internet if so required, where suitable software exists in the communications device.

5

Alternatively, users can connect their target systems for remote evaluation by, for example, the manufacturer. Yet another alternative is to provide the facility to upgrade or otherwise modify the contents of

10 stored information in the target.